Customized Workstations / Worktables



Features

- Workstations customized for your specific applications
- Robotunits modular systems are flexible allowing for modifications if applications change
- Smart extrusion technology means all parts and accessories are compatible with no adapters necessary
- Strong fastening technology means your application will be 100% play-free, accurate and aligned
- All applications are vibration resistant with strength comparable to welded connections

Adjustable desktop height



Tool balancer with horizontal slide



Slotted tabletop & scrap hopper



Adjustable lights





Valve/Cartridge System



Various Accessories Available





Please contact Izumi International, Inc. for special requirements



IZUMI INTERNATIONAL, INC.

1 Pelham Davis Circle, Greenville, SC 29615 USA Tel: 864-288-8001 Fax: 864-288-7272 E-mail: us-sales@izumiinternational.com Web: www.izumiinternational.com

IZUMI INTERNATIONAL CO., LTD.

3-20-10 Toyosaki, Kita-ku, Osaka, Japan Tel: 06-6375-4116 Fax: 06-6375-4117 E-mail: jp-sales@izumiinternational.com Web: www.izumiinternational.co.jp

Customized Workstations / Worktables



ustomer:	Contact Name:	Phone:
/orkstation Name:	Qty. Needed:	Future Qty. Needed:
What operations will be performed at	The length of the work surface should	Indicate workstation side and back
the workstation?	be:	covers if needed:
☐ Mechanical assembly	☐ 36 inches ☐ 48 inches	☐ None required
☐ Circuit board assembly	☐ 60 inches ☐ 72 inches	☐ Right Side ☐ Left side
Testing Inspection	☐ 60 inches ☐ 72 inches ☐ 96 Inches ☐ Other:	☐ Right Side ☐ Left side ☐ Full back ☐ Lower back
☐ Testing ☐ Inspection ☐ Rework ☐ Packaging		Upper back
☐ Design work ☐ Trim work	The depth of the work surface should	Partial opening in the back
Other:	be:	Other:
Olici.	20 inches 22 inches	_ outer.
What assembly processes will be	☐ 24 inches ☐ 26 inches	Indicate the size and location of
done at the workstation?	24 inches 26 inches 28 inches Other:	shelving if needed:
Adhesive bonding / Gluing		☐ None required
Screw driving Trimming	The height of the work ourface abouted	Shelf 1
Screw driving I miniming	The height of the work surface should	
Riveting Welding Soldering Wiring Sonding Cleaning	be adjustable from to	Length: Width: Qty.:
Soldering wiring	inches.	Location:
Sanding		Shelf 2
Other:	The workstation should be equipped	Length: Width: Qty.:
	with rear uprights that are	Shelf 3
Do any of the following environmental	inches tall.	Length: Width: Qty.:
areas or factors apply?		Location:
☐ Clean room ☐ Lab	The height of the work surface should	Shelf 4
Plant floor Maint. shop	be adjusted using	Length: Width: Qty.:
☐ Excessive dust ☐ Oil / grease	☐ Manually, with tools	Location:
☐ UV exposure ☐ Wash down	☐ Manually, with hand locks	Other:
Other:	Mechanical crank	A CONTRACTOR CONTRACTO
	☐ Electric lifts ☐ Pneumatic lifts	Lighting:
Work will be conducted while:	Hydraulic lifts	☐ None required
Standing Seated	Other:	Fluorescent
Standing Scatca	Guidi.	Fixed, 2 bulb X
Usus manu products will be	The work ourface abouted have	Fixed, 4 bulb X
How many products will be	The work surface should have	
assembled at the workstation?	☐ Flat edges ☐ Rounded edges	Adjustable, 2 bulb X
	☐ Square corners ☐ Rounded corners	Track
How often are changeovers:	pg 20 (2011) 10 (1911) 10	☐ Halogen ☐ Incandescent
	Will the work surface need to tilt?	☐ 1 Track ☐ 2 Track
Most of the products assembled at the	Yes No	Number of fixtures:
workstation will fit into a:	90 845800 30383004	(65.8500.500.500.500.000.00
6 inch cube 12 inch cube	What type of work surface is needed?	Accessories:
24 inch cube 36 inch cube	☐ Plastic laminate ☐ Static-dissipative	☐ Accessory mounting bars
48 inch cube Other:	☐ Melamine ☐ Plywood	Accessory shelves
Length: Width: Depth:	☐ Carpet ☐ Rubber/vinyl ☐ Aluminum ☐ Stainless steel	☐ Tool trolley rail system
	☐ Aluminum ☐ Stainless steel	☐ Table extensions
Most products assembled at the	☐ HDPE ☐ UHMW	Protective table mats
workstation weigh:	☐ Ball transfer	Storage cabinets
☐ Under 1 pound ☐ 1 to 10 pounds	Other.	☐ Document holder
11 to 50 pounds 51 to 100 pounds		Computer mount
Other:	Is a table top insert required?	☐ Keyboard mount
	Yes No	Plant air regulator & distribution
Will the work station be moved		☐ Tool support arm
	Insert Size: Length: Width:	Coldodos fumo removal avetara
frequently?	Miles Administration of the control	Soldering fume removal system
☐ Yes ☐ No	What type of insert is needed?	Monitor Mount Fan
Date and a state of the state o	☐ Vinyl coated screen	☐ Drawers ☐ Footrest
Parts and materials will arrive at the	Expanded metal	Floor mats Magnifier lamp
workstation from the	☐ Fiberglass grate ☐ Plastic grate	Power strip Phone jack
☐ Left ☐ Right ☐ Front ☐ Back	☐ Other:	LAN jack Peg board
Parket and a second sec		☐ Parts bins ☐ Clip board
Assemblies will leave the workstation	What opening size is needed in the	☐ Tool holders ☐ Tool baskets
from the	insert screen or grate material?	☐ Tumtable ☐ Tool balancer
☐ Left ☐ Right ☐ Front ☐ Back	Length: Width: Dia.:	☐ Trash can ☐ Tool retractor
The second secon		Scrap hopper Cup holder
What other equipment will the	The workstation should be on	☐ Stools ☐ Chairs
workstation interface with?	Levelers	Spot lighting Sign boards
Other workstations	Swivel casters X	Bench vice Scrap bin
Conveyor Flow rack	Swivel casters × Swivel casters ×	☐ Floor anchors ☐ Handles
☐ Mobile cart ☐ Hoist	☐ Swiver casters with brake ∧	Clock Radio
☐ Mobile cart ☐ Hoist ☐ Other:	Fixed casters X	
I Tother.	I Fixed casters with brake X	Tape dispenser



IZUMI INTERNATIONAL, INC.

Please contact Izumi International, Inc. for special requirements

3-20-10 Toyosaki, Kita-ku, Osaka, Japan Tel: 06-6375-4116 Fax: 06-6375-4117 E-mail: jp-sales@izumiinternational.co.jp Web: www.izumiinternational.com